



Specifications / Special Features:

MODEL NO. **KC-JC3140**

IMAGE SENSOR: **1/3" SHARP Super CCD**

DSP: Sharp

CCD TOTAL PIXELS: NTSC: 542 (H)x492 (V) PAL: 512 (H) x582 (V)

SCANNING SYSTEM: NTSC: 525 lines, 60 fields/sec PAL: 625 lines, 50 fields/sec

SYNC SYSTEM: Internal

MINIMUM ILLUMINATION: 0.8 Lux F1.2

RESOLUTION: 420 TV Line

WHITE BALANCE: ATW / AWC Switchable

GAIN CONTROL: AGC ON / OFF switchable

S/N RATIO: 48dB (AGC OFF)

ELECTRONIC SHUTTER: NTSC: 1/60~1/120,000 sec. PAL: 1/50~1/120,000 sec.

AUTO IRIS: VIDEO / DC

LENS MOUNT: C/CS Vari-focal Mount

B.L.C. FUNCTION: ON/OFF switchable

MIRROR FUNCTION: ON/OFF switchable

VIDEO OUTPUT: Composite 1.0V p-p at 75 ohm

GAMMA CORRECTION: 0.45

OPERATION TEMPERATURE: -10°C to 50°C

OPERATIONAL HUMIDITY: < 85%RH

POWER SUPPLY: DC12V±1V, 150mA

DIMENSIONS(φX H): 138X78

Weight: 540g