



Specifications / Special Features:

MODEL NO. **KC-R3148**

IMAGE SENSOR: **1/3" Sony Super HAD CCD**

DSP: Sony

CCD TOTAL PIXELS: NTSC: 811 (H) X 508 (V) PAL: 795 (H) X 596 (V)

SCANNING SYSTEM: NTSC: 525 lines, 60 fields/sec PAL: 625 lines, 50 fields/sec

SYNC SYSTEM: Internal

MINIMUM ILLUMINATION: 0.8Lux F1.2 0 Lux(IR ON)

RESOLUTION: 480 TV Line

WHITE BALANCE: ATW / AWC switchable

GAIN CONTROL: AGC ON / OFF switchable

S/N RATIO: 48dB (AGC OFF)

ELECTRONIC SHUTTER: NTSC: 1/60~1/120,000 sec. PAL: 1/50~1/120,000 sec.

B.L.C. FUNCTION: ON/OFF switchable

MIRROR FUNCTION: ON/OFF switchable

VIDEO OUTPUT: Composite 1.0V p-p at 75 ohm

GAMMA CORRECTION: 0.45

LENS: Board Lens mount

IR LED: (850nm, 15°) x 12 LEDs (850nm, 45°) x 12 LEDs

VISIBLE DISTANCE: 25m (Lens 12mm)

OPERATION TEMPERATURE: -10°C TO 50°C

OPERATIONAL HUMIDITY: < 85%RH

POWER SUPPLY: DC12V±1V / 350mA

DIMENSIONS(L x W x H): 105X72X140

Weight t: 580g