



**Specifications / Special Features:**

---

MODEL NO. **KC-R4140**

IMAGE SENSOR: **1/4" Sharp Super CCD**

---

DSP: Sharp

---

CCD TOTAL PIXELS: NTSC: 542 (H) x 492 (V) PAL: 582 (H) x 512 (V)

---

SCANNING SYSTEM: NTSC: 525 lines, 60 fields/sec PAL: 625 lines, 50 fields/sec

---

SYNC SYSTEM: Internal

---

MINIMUM ILLUMINATION: 0.8 Lux F1.2 0 Lux(IR ON)

---

RESOLUTION: 420 TV Line

---

WHITE BALANCE: ATW / AWC switchable

---

GAIN CONTROL: AGC ON / OFF switchable

---

S/N RATIO: 48dB (AGC OFF)

---

ELECTRONIC SHUTTER: NTSC: 1/60~1/120,000 sec. PAL: 1/50~1/120,000 sec.

---

B.L.C. FUNCTION: ON/OFF switchable

---

MIRROR FUNCTION: ON/OFF switchable

---

VIDEO OUTPUT: Composite 1.0V p-p at 75 ohm

---

GAMMA CORRECTION: 0.45

---

LENS: Board Lens mount

---

IR LED: (850nm, 15°) x 12 LEDs (850nm, 45°) x 12 LEDs

---

VISIBLE DISTANCE: 25m (Lens 12mm)

---

OPERATION TEMPERATURE: -10°C TO 50°C

---

OPERATIONAL HUMIDITY: < 85%RH

---

POWER SUPPLY: DC12V±1V / 350mA

---

DIMENSIONS(L x W x H): 105X72X140

---

Weight t: 580g